



Versatronic

4-channel measuring and control unit in modular design

- ▲ Chemical-resistant housing for wall mounting or control cabinet installation
- ▲ 5.5 inch display with touch control
- ▲ Large terminal compartment
- ▲ Acquisition and processing of up to 4 variables (conductivity, pH, redox, Cl, ClO₂, peracetic acid, ...)
- ▲ Features per channel:
 - 1 analysis input
 - 1 temperature input
 - 1 release input
 - 1 freely programmable controller
 - 1 or more control outputs
 - 1 standard signal output (0/2-10 V or 0/4-20 mA)
- ▲ Device configuration using the setup program on your PC/laptop; data transfer to the device via USB cable or USB-stick (optional)
- ▲ Various interfaces such as RS 422/485, USB, Profibus (optional), LAN with integrated Web Server (optional)



The Versatronic modular system:

Measurement

Control

ClO₂, PAA and chlorine



Inductive and conductive conductivity



pH, Redox and temperature



Diaphragm metering pumps



Valves





Standard signal
Transfer the measured values to a primary control



RS 422/485 or USB
Data transfer via interface cable or USB stick



Profibus
Transfer the measured data and status messages to a PROFIBUS DP master



Screen logger
Integrated into the device with internal data storage of up to one year



LAN (with integrated Web Server)

- Remote querying of device states
- Alarm notification by email or SMS
- Remote error analysis based on the alarm lists or the logger data



Communication

Registration

Ecolab Engineering GmbH
 Postfach 1164 83309 Siegsdorf
 Tel. +49 8662 61 0
 engineering-mailbox@ecolab.com
 www.ecolab-engineering.com
 www.ecolab.com