



EcoPro / EcoAdd

The New Pump Generation

- ▲ Variable arrangement of control unit and mounting console
- ▲ Electronically adjustable metering capacity from 1:100
- ▲ Different metering modes adjustable (e.g. for high-viscosity products)
- ▲ USB interface
- ▲ Future-oriented safety and communication tools
- ▲ Multicolor touch display



Technical data

Electrical versions:



EcoPro

Keys / settings:
LEDs:
Inputs:

on/off, test, viscosity high/low, 1:100
operation, viscosity high/low, alarm
release



EcoAdd

Keys / settings:
Display:
Operation mode:
Inputs:
Outputs:
Communication:
Option:

on/off, 4 viscosity modes, 5 operating modes, 1:100
touch display
manual, pulse, current, timer, charge
release, pulse, current, charge, level, flow, diaphragm break
stroke signal, alarm
USB, CAN Bus
Bluetooth extension module

General data:

Pump type		5	11	30	50	120
Pump capacity:	l/h	0.05 - 5	0.11 - 11	0.3 - 30	0.5 - 50	1.2 - 120
max. metering back pressure	bar	10	10	3	10	3
Connection thread		3/8"	3/8"	5/8"	5/8"	1 1/4"
Reproductivity		+- 3%				
max. suction height	m	2				
max. metering frequency	1/min	171	190	171	158	171
max. viscosity	mPas	500	500	250	500	250
max. ambient temperature	°C	2 - 45				
Power supply	V	100 - 240 V +10% 50/60 Hz				
Safety type		IP 65				

Variable structure



Upgrade from **EcoPro** to **EcoAdd**



Flexible installation

Ecolab Engineering GmbH
Postfach 1164 83309 Siegsdorf
Tel. +49 8662 61 0
engineering-mailbox@ecolab.com
www.ecolab-engineering.com

