

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0.98 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1030

ECOLAB Engineering GmbH  
D-83313 Slegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 50 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,88 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1029

ECOLAB Engineering GmbH  
D-83113 Siegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 51 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 16.12.22

Prüfer Sollweider

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906



OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 26022 / 1028

260162

ECOLAB Engineering GmbH  
D-83313 Siedsdorf



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 51 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 16.12.22

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/BI-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2800 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 708579 / 25022 / 1027

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 53 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollgader

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1026

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 52 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906



OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1025

280162

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 52 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8I-99-2600p-P

materials of construction:	PVC, FKM HF, PVDF, ceramic
signal output (standard):	0,38 ml/pulse, 2600 pulses/l
max. pump size:	11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction:	PNP
prod. code:	01 / 706579 / 25022 / 1024

ECOLAB Engineering GmbH  
D-83313 Siegedorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 52 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollerseder



# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1023

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 50 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollerseder



# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,98 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1022

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 53 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 16.12.22

Prüfer Sollersoder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W37262906

OGM PLUS 00112VCFPPVKE-G1/8I-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1021

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 52 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 16.12.22

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6l-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1020

ECOLAB Engineering GmbH

D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 52 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2800p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2800 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1019

ECOLAB Engineering GmbH  
D-83313 Slegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 56 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 16.11.22

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1018

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



280162

Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 53 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 16.12.22

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1017

ECOLAB Engineering GmbH  
D-63313 Siegsdorf



280162

Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 50 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollweider

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112



W3T262906

OGM PLUS 00112VCFPPVKE-G1/8I-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1016

280162

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 52 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollereder



# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1015

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 51 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 16.12.22

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1014

ECOLAB Engineering GmbH  
D-83313 Slegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 51 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6I-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1013

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



260162

Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 50 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,88 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1012

ECOLAB Engineering GmbH  
D-83313 Siegedorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 50 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollweider

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1011

ECOLAB Engineering GmbH  
D-83313 Slegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 52 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 14.12.22

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1010

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 51 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1009

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 50 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollerseder



# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1008

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



280162

Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 53 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1007

ECOLAB Engineering GmbH  
D-83313 Siedsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 53 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollgeder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/BI-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,33 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1006

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 53 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollreder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

**W3T262906**

OGM PLUS 00112VCFPPVKE-G1/8I-99-2600p-P

materials of construction:	PVC, FKM HF, PVDF, ceramic
signal output (standard):	0,38 ml/pulse, 2600 pulses/l
max. pump size:	11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction:	PNP
prod. code:	01 / 706579 / 25022 / 1005

ECOLAB Engineering GmbH  
D-83313 Slegsdorf



280162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 53 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,98 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1004

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



280162

Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 52 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollercedes

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

**W3T262906**

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,98 ml/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706576 / 26022 / 1008

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 50 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6l-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0.98 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 706579 / 25022 / 1002

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 53 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollreider



# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/81-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic  
signal output (standard): 0,38 m/pulse, 2600 pulses/l  
max. pump size: 11,2 / 13,5 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01 / 706579 / 25022 / 1001

ECOLAB Engineering GmbH  
D-83313 Slegsdorf



260162



Anlaufgrenze 0,8 [l/h]\*  
lower measuring range limit

Impulszahl 50 [n/min]  
pulse rate

bei 1,25 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 15.12.22

Prüfer Sollerseder